



■ **UT331**



■ **UT332**

SPECIFICATIONS

DATA HOLD MAX MIN USB

Specifications	Range	Best Accuracy		
Model		UT331	UT332	
Temperature	Range	-20°C~70°C(-4°F~158°F)	√	√
	Accuracy	-20°C~0°C	±1°C	±1°C
		0°C~40°C	±0.5°C	±0.5°C
		40°C~70°C	±1°C	±1°C
Resolution	0.1°C/0.1°F	√	√	
Relative Humidity	Range	0%RH~100%RH	√	√
	Accuracy	10%RH~90%RH	±3.5%RH	±2.5%RH
		<10%RH or >90%RH	±5%RH	±5%RH
	Resolution	0.1%RH	√	√
Features				
°C/°F Selection		√	√	
Response Time	Around 10 Seconds	√	√	
Humidity Offset Settings		√	√	
Temperature Offset Settings		√	√	
Dew Point Offset Settings		√	√	
Auto Power Off		√	√	
Power Saving Mode			√	
Data Hold		√	√	
MAX/MIN		√	√	
Data Storage		100	100	
Data Recall		√	√	
USB Interface		√	√	
Auto Record Time Setup		√	√	
LCD Backlight		√	√	

GENERAL CHARACTERISTICS

Power	1.5V Batteries (LR03) × 4
LCD Size	26.5mm × 35.5 mm
Product Color	Red and Grey
Product Net Weight	130 g
Product Size	185mm × 54.8mm × 33.8mm
Standard Accessories	Batteries, USB Interface Cable, PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	555mm × 430mm × 288 mm (0.069CBM Per Standard Carton)
Standard Carton Gross Weight	10 Kg